

Schnelldicht

Sealing Mortar

Quick-setting, fibre-reinforced and polymer-enhanced Sewer Structural Mortar



- Seals leaking surfaces, stops inflowing water
- Contains special fibres
- Use only in wet environments
- Accelerator for IBW® Sewer Rehab Mortar

Properties

- stops and seals off water ingress
- waterproof up to 5 bars (= 50 m hydraulic head)
- very fast-setting
- shrinkage-free

Resistance

- resistance class III (GSTT Information Bulletin No 18)
- resistance class III (DWA-Information Bulletin M 143-17)
- Exposition class to DIN EN 206-1 und DIN 1045-2
- WF

Technical Information

Processing window:	max. 1 minute
Water penetration depth:	5 mm (at 5 bars according to DIN EN 12390)
Grain size:	< 1 mm
Storage:	store in dry areas only
Storage life:	approx. 6 months
Supply packaging:	10 kg buckets

Hinweise: Please note:

The information provided in this data sheet are general indications based on tests and site experience. They are not however to be construed as being directly applicable to the user's intended application. As the data given are average figures determined at normal ambient conditions (20 °C / 65 % relative humidity), deviations may be encountered in individual cases and under actual site conditions. In any work involving this product, please observe our processing recommendations, all applicable national and European guidelines, official recommendations and standards as well as accepted engineering practice. Suitability for the user's intended application must be verified by tests prior to use. Our liability with regard to this product shall be limited exclusively to product quality, i.e. conformance with the technical data of the product represented above. We reserve the right to implement modifications without prior notice in accordance with ongoing development. This technical data sheet supersedes and renders invalid all previously issued versions. Issue: 04/12